

# P/N NAS463YDD10M

## **Description**

Nut Length: 1-5/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS463YDD10M
Minimum Qty (MOQ):	60 EA
NSN:	5310-00-527-5287
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS463YDD10M Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.049 Inches Minimum And 1.079 Inches Maximum
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Plate Width:	0.391 Inches Minimum And 0.421 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-b-255 Fed Spec 1st Material Response Overall Or Qq-a-362 Fed Spec 2nd Material Response Overall Or Qq-a-287,comp 7075 Fed Spec 3rd Material Response Overall

### **How to Order**

Order this nut spacer from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS463YDD10M">https://military-fasteners.com/bolts/machine+bolts/NAS463YDD10M</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.