

Description

Nut Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463YDD416L
Minimum Qty (MOQ):	55 EA
NSN:	5310-00-680-7395
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS463YDD416L Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.235 Inches Minimum And 1.265 Inches Maximum
Thru-hole Diameter:	0.322 Inches Minimum And 0.332 Inches Maximum
Plate Thickness:	0.012 Inches Minimum And 0.020 Inches Maximum
Plate Width:	0.485 Inches Minimum And 0.515 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.497 Inches Minimum And 0.503 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/3,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t3 Or T4 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,t6 Fed Spec 3rd Material Response Overall

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463YDD416L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.