

Description

Fastener Length: 2-1/2", Thread: 5/8-18, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4641032
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-477-1612
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS464-10-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	2.500 Inches Nominal
Head Style:	Hexagon
Head Height:	0.312 Inches Nominal
Width Between Flats:	0.938 Inches Nominal
Grip Diameter:	0.624 Inches Nominal
End Item Identification:	Seaking Airframe, National Aerospace Standards
Nominal Thread Diameter:	0.625 Inches
Grip Length:	2.000 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	15050 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Threads
Surface Treatment:	Cadmium Head
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec All Treatment Responses Head
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec All Treatment Responses Threads
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464-10-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.