

## P/N NAS464-10-43

### **Description**

Fastener Length: 3-3/16", Thread: 5/8-18, Thread Length: 1/2

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS4641043                                |
|-------------------------|---|
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5306-00-551-0015                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS464-10-43 Specifications

| Thread Class:  | 3a   |
|--|--|
| Thread Direction:  | Right-hand   |
| Thread Length:   | 0.500 Inches Minimum   |
| Fastener Length:   | 3.188 Inches Nominal   |
| Head Style:  | Hexagon  |
| Head Height:   | 0.312 Inches Nominal   |
| Width Between Flats:   | 0.938 Inches Nominal   |
| Grip Diameter:   | 0.6240 Inches Nominal  |
| <b>Shank Unthreaded Hole Diameter:</b>                                 | 0.141 Inches Nominal First Hole  |
| Single Shear Strength:   | 29150 Pounds Per Square Inch   |
| Nominal Thread Diameter:   | 0.625 Inches   |
| Grip Length:   | 2.688 Inches Nominal   |
| Thread Quantity Per Inch:  | 18   |
| Minimum Tensile Strength:  | 160000 Pounds Per Square Inch  |
| Hardness Rating:   | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| Distance From Head Largest<br>Bearing Surface To Shank Hole<br>Center: | 3.000 Inches Nominal First Hole  |
| Material:  | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall  |
| Material Document And Classification:                                  | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall |
| Surface Treatment:   | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And Classification:                         | Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall  |
| Thread Series Designator:  | Unf  |
|  |  |

# **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS464-10-43">https://military-fasteners.com/bolts/machine+bolts/NAS464-10-43</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.