

P/N NAS464-3-12

Military-Fasteners.com

Description

Fastener Length: 1-3/32", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS464312
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-639-2270
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS464-3-12 Specifications

Inread Class:asThread Viction:Right-handThread Length:0.344 Inches MinimumFasteer Length:1.094 Inches NominalHead Style:Hexa gonHead Height:0.994 Inches NominalWidth Between Flats:0.375 Inches Nominal InstOrip Diameter:0.370 Inches Nominal Irist HoleShark Unthreaded Hole Diameter:0.700 Inches Nominal Irist HoleSingle Shear Strength:0.200 Inches Nominal Irist HoleSingle Shear Strength:0.300 Inches Nominal Irist HoleSingle Shear Strength:0.300 Inches Nominal Irist HoleThread Diameter:0.700 Inches Nominal Irist HoleSingle Shear Strength:0.300 Inches NominalThread Diameter:0.700 Inches Nominal Irist HoleSingle Shear Strength:0.300 Inches NominalThread Diameter:0.700 Inches Nominal Irist HoleThread Olamity Per Inch:32Distance From Head LargestBearing Surface To Shank HoleDistance From Head LargestSale Inches Nominal Irist HoleBearing Surface To Shank HoleSteel Comp 4140 Overall Or Steel Comp EI340 Overall Or Steel Comp B735 Overall Or Steel Comp 8735Surface Treatment:Cadmium ThreadsSurface Treatment:Cadmium Theed Steel Comp 40.37 Overall Or Mill-5000 Mill Spec 2nd Material Response Overall Or Mill-8033 Mill Spec 3rdMaterial Bocument And Classification:Ope-116.1ype 2.class 3 Fed Spec Single Treatment Response HeadSurface Treatment:Cadmium ThreadsSurface Treatment:Cadmium Thread Steel Spec Single Treatment Response Threads		
Thread Length:0.344 Inches MinimumFaster Length:1094 Inches NominalHead Style:0.094 Inches NominalHead Height:0.094 Inches NominalWitht Between Flats:0.375 Inches NominalGrip Diameter:0.1894 Inches NominalStank Unthreaded Hole Diameter:0.190 Inches Nominal First HoleSingle Shear Strength:2600 Pounds Per Square InchMinimum Tensile Diameter:0.190 Inches NominalOring Length:0.190 Inches NominalThread Quantity Per Inch2500 Pounds Per Square InchMinimum Tensile Strength:0.600 Pounds Per Square InchBistens Form Head Langest0.600 Pounds Per Square InchHardens Rating:0.500 Rockwell C Maximum Overall And 40.0 Rockwell C Maximum OverallBistens From Head Langest0.938 Inches Nominal First HoleBistens From Head Langest0.938 Inches Nominal First HoleChereir:0.938 Inches Nominal First HoleBistens From Head Langest0.938 Inches Nominal First HoleChereir:0.938 Inches Nominal Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 5nd Material Response Overall Or Mil-s-500	Thread Class:	За
Pastener Length:1.094 Inches NominalHead Style:HexagonHead Height:0.094 Inches NominalWidth Between Flats:0.357 Inches NominalOriginater:0.1894 Inches NominalStank Unthreaded Hole Diameter:0.700 Inches Nominal First HoleStank Unthreaded Hole Diameter:0.900 Inches Nominal First HoleStank Unthreaded Hole Diameter:0.900 Inches Nominal First HoleStank Unthread Diameter:0.900 Inches Nominal First HoleStank Unthread Diameter:0.900 Inches Nominal First HoleStank Unthread Diameter:0.900 Inches NominalOptimal Thread Diameter:0.900 Inches NominalBrain Diameter:0.900 Inches NominalStanker Strength:18000 Pounds Per Square InchBrain Diameter:0.900 Inches Stating:Brain Surface To Shank Hole3000 Pounds Per Square InchBrain Surface To Shank Hole303 Inches Nominal First HoleStatice From Head Largets Bearing Surface To Shank HoleStatice Comp 4140 Overall Or Steel Comp El340 Overall Or Steel Comp 5150 Overall Or Steel Comp 8735 Mil Spec 3th Material Response Overall Or Mil-s-6036 Mil Spec 3th Material Response Overall Or Mil-s-6036 Mil Spec 4th Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-60	Thread Direction:	Right-hand
Head Style:HexagonHead Height:0.094 Inches NominalWidth Between Flats:0.375 Inches NominalGrip Diameter:0.1894 Inches Nominal First HoleGrip Diameter:0.000 Inches Nominal First HoleShank Unthreaded Hole Diamet0.070 Inches Nominal First HoleSingle Shear Strength:2600 Pounds Per Square InchOminal Thread Diameter:0.190 Inches NominalGrip Length:0.190 Inches NominalThread Quantity Per Inch32Minimu Tensile Strength:6.0000 Pounds Per Square InchHardness Rating:6.0.000 Pounds Per Square InchHardness Rating:6.0.000 Pounds Per Square InchBearing Surface From Head Largest Bearing Surface Toshank Hole9.398 Inches Nominal First HoleNeterial:0.938 Inches Nominal First HoleMaterial Bocument And Classification:Seel Comp 4140 Oxtel Comp E340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallSurface Treatment:Gamium ThreadsSurface Treatment:Camium ThreadsSurface Treatment:Camium ThreadsSurface Treatment:Gamium Threads <td< td=""><th>Thread Length:</th><td>0.344 Inches Minimum</td></td<>	Thread Length:	0.344 Inches Minimum
Head Height:0.094 Inches NominalWith Between Flats:0.375 Inches NominalGrip Diameter:0.1894 Inches Nominal First HoleStank Unthreaded Hole Diamete:0.700 Inches Nominal First HoleSingle Shear Strength:0.500 Pounds Per Square InchNominal Thread Diameter:0.190 Inches Nominal0.190 Inches Nominal First Hole0.700 Inches NominalThread Quantity Per Inch:0.750 Inches Nominal16000 Pounds Per Square Inch16000 Pounds Per Square InchHardness Rating:0.600 Rounds Per Square InchHardness Rating:0.380 Inches Nominal First HoleBearing Surface To Shank Hole0.381 Inches Nominal First HoleChreat Part Heid Largest Bearing Surface To Shank Hole0.381 Inches Nominal First HoleRaterial:See Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 8740 Overall Or Mil-s-6029 Mil Spec 3th Material Response Overall Or Mil-s-6029 Mi	Fastener Length:	1.094 Inches Nominal
Width Between Flats:0.375 Inches NominalGrip Diameter:0.1894 Inches Nominal First HoleShank Unthreaded Hole Diameter:0.070 Inches Nominal First HoleSingle Shear Strength:2690 Pounds Per Square InchNominal Thread Diameter:0.190 InchesOrigi Length:0.750 Inches NominalThread Quantity Per Inch:32Bearing Sturface Treatmeth60000 Pounds Per Square InchHardenss Ratting:0.6000 Pounds Per Square InchHardenss Ratting:0.6000 Pounds Per Square InchHardenss Ratting:0.6000 Pounds Per Square InchHardenss Ratting:0.903 Inches Nominal First HoleDistance From Head LargestSteel Comp 1140 Overall On Steel Comp E4340 Overall On Steel Comp 8735 Overall On Steel Comp 8735 Overall On Steel Comp 4037 OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall On Steel Comp 6150 Overall On Steel Comp 8735 Overall On Mil-s-6098 Mil Spec 2nd Material Response Overall On Mil-s-6098 Mil Spec 3th Material Response Overall On Mil-s-6098 Mi	Head Style:	Hexagon
Grip Dameter:0.1894 Inches NominalShank Unthreaded Hole Diameter:0.070 Inches Nominal First HoleSingle Shear Strength:0.690 Pounds Per Square InchNominal Thread Diameter:0.190 InchesOrg Length:0.750 Inches NominalThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:6.0.80ckwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole	Head Height:	0.094 Inches Nominal
Shank Unthreaded Hole Diameter:0.070 Inches Nominal First HoleSingle Shear Strength:690 Pounds Per Square InchNominal Thread Diameter:0.190 InchesOrig Length:0.190 Inches NominalThread Quantity Per Inch:32Biolor Dounds Per Square Inch160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Center:0.938 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8730 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Steel Comp 4140 Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049	Width Between Flats:	0.375 Inches Nominal
Single Shear Strength:2600 Pounds Per Square InchNominal Thread Diameter:0.190 InchesOrip Length:0.750 Inches NominalThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.60 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallBearing Surface To Shank Hole0.338 Inches Nominal First HoleStering:0.398 Inches Nominal First HoleMaterial:See Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Mil-s-6030 Mil Spec 1st Material Response Overall Or Mil-s-6009 Mil Spec 4th Material Response Overall Or Mil-s-6049	Grip Diameter:	0.1894 Inches Nominal
Nominal Thread Diameter:0.190 InchesGrip Length:0.750 Inches NominalThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole0.938 Inches Nominal First HoleOrester InchSeel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallRaterial Document And Classification:Mils-S626 Mil Spec 1st Material Response Overall Or Mils-S000 Mil Spec 2nd Material Response Overall Or Mils-S6098 Mil Spec 4th Material Response Overall Or Mils-8695 Mil Spec 3th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Qu-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qu-p-416,type 2,class 3 Fed Spec Single Treatment Response Head	Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Grip Length:0.750 Inches NominalThread Quantity Per Inch:32Minimu Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest center:0.338 Inches Nominal First HoleMaterial:Seel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mils-s626 Mil Spec 1st Material Response Overall Or Mils-s5000 Mil Spec 2nd Material Response Overall Or Mils-s6098 Mil Spec 4th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6098 Mil Spec 4th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6098 Mil Spec 4th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6098 Mil Spec 4th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6098 Mil Spec 4th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6049 Mil Spec 5th Material Response Overall Or Mils-s6049 Mils Spec 5th M	Single Shear Strength:	2690 Pounds Per Square Inch
Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:0,938 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Ov	Nominal Thread Diameter:	0.190 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:0,938 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial:Mil-s-6626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6805 Mil Spec 3rd Material Response Overall Or Mil-s-6008 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6895 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response ThreadsSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Grip Length:	0.750 Inches Nominal
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:.938 Inches Nominal First HoleMaterial:.938 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8736 OverallMaterial:Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-86098 Mil Spec 4th Material Response Overall Or Mil-s-86098 Mil Spec 3th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole0.938 Inches Nominal First HoleMaterial:0.938 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6009 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center:0.938 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8736 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Bearing Surface To Shank Hole	0.938 Inches Nominal First Hole
Material Document And Classification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Head	Material:	
Surface Treatment Document And Classification:Cadmium HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads		Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or
Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Head Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Surface Treatment:	Cadmium Threads
Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Head Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Surface Treatment:	Cadmium Head
Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads		Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Head
Thread Series Designator: Unf		Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS464-3-12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.