

Description

Fastener Length: 19/32", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS46434 |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5306-00-638-4287 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS464-3-4 Specifications

| | |
|-------------------------------------------------------------------------|-------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.344 Inches Maximum |
| Fastener Length: | 0.594 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.094 Inches Nominal |
| Width Between Flats: | 0.375 Inches Nominal |
| Grip Diameter: | 0.1889 Inches Minimum And 0.1894 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Nominal First Hole |
| Single Shear Strength: | 2690 Pounds Per Square Inch |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.250 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.438 Inches Nominal First Hole |
| Material: | Steel Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464-3-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.