

P/N NAS464-3A10

Description

Fastener Length: 0-63/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS4643A10

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-285-7528

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS464-3A10 Specifications

hread Direction: Right-hand hread Length: 0.327 Inches Minimum And 0.374 Inches Maximum astener Length: 0.953 Inches Minimum And 0.100 Inches Maximum lead Style: Hexagon lead Height: 0.078 Inches Minimum And 0.110 Inches Maximum lead Height: 0.078 Inches Minimum And 0.1377 Inches Maximum lead Height: 0.365 Inches Minimum And 0.377 Inches Maximum lead Height: 0.1889 Inches Minimum And 0.1894 Inches Maximum lingle Shear Strength: 0.1889 Inches Minimum And 0.1894 Inches Maximum lingle Shear Strength: 0.625 Inches Minimum And 0.1894 Inches Maximum lingle Shear Strength: 0.625 Inches Nominal Intread Quantity Per Inch: 32 linimum Tensile Strength: 160000 Pounds Per Square Inch lardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall lardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 lasterial Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5004 Mil Spec 3nd Material Response Overall Or Mil-s-5009 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3th Material Response Overall urface Treatment: Cadmium Threads And Chromate Threads urface Treatment: Cadmium Head And Chromate Head urface Treatment Document And lassification: Unif	Three d Class.	
Aread Length: astener Length: astener Length: bead Style: lead Style: lead Height: 0.978 Inches Minimum And 0.101 Inches Maximum lead Style: lead Height: 0.978 Inches Minimum And 0.110 Inches Maximum lead Style: lead Height: 0.978 Inches Minimum And 0.110 Inches Maximum lead Style: lead Height: 0.978 Inches Minimum And 0.197 Inches Maximum lead Height: 0.1889 Inches Minimum And 0.1894 Inches Maximum lead Style: lingle Shear Strength: 0.1889 Inches Minimum And 0.1894 Inches Maximum lead Style: lingle Shear Strength: 0.190 Inches lead Height: 0.190 Inches lead	Thread Class:	
lead Style: Heagth: 0.953 Inches Minimum And 1.000 Inches Maximum lead Style: Hexagon lead Height: 0.078 Inches Minimum And 0.110 Inches Maximum lead Height: 0.365 Inches Minimum And 0.377 Inches Maximum lifty Dlameter: 0.1889 Inches Minimum And 0.1894 Inches Maximum lifty Dlameter: 0.1889 Inches Minimum And 0.1894 Inches Maximum lifty Dlameter: 0.190 Inches Minimum And 0.1894 Inches Maximum lifty Dlameter: 0.190 Inches Maximum lifty Dlameter: 0.190 Inches Maximum lifty Dlameter: 0.190 Inches lifty Length: 0.625 Inches Nominal lifty Dlameter: 0.190 Inches lifty Length: 0.625 Inches Nominal lifty Dlameter: 0.565 Inches Nominal lifty		
lead Style: Hexagon lead Height: 0.078 Inches Minimum And 0.110 Inches Maximum lift between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum lift blameter: 0.1889 Inches Minimum And 0.1894 Inches Maximum lift blameter: 0.190 Inches Minimum And 0.1894 Inches Maximum lift blameter: 0.190 Inches Minimum And 0.1894 Inches Maximum lift blameter: 0.190 Inches lift blameter: 0.190 Inches lift blameter: 0.625 Inches Nominal lift blameter: 0.625 Inches National lift blameter: 0.625 Inches Natio	Thread Length:	0.327 Inches Minimum And 0.374 Inches Maximum
lead Height: 0.078 Inches Minimum And 0.110 Inches Maximum Vidth Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum irip Diameter: 0.1889 Inches Minimum And 0.1894 Inches Maximum irip Diameter: 0.1890 Inches Minimum And 0.1894 Inches Maximum irip Length: 0.625 Inches Nominal irip Length: 0.625 Inches Minimum And 0.1894 Inches Maximum irip Length: 0.625 Inches Nominal irip Length: 0.625 Inches Maximum irip Length: 0	Fastener Length:	0.953 Inches Minimum And 1.000 Inches Maximum
Nidth Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum 0.1889 Inches Minimum And 0.1894 Inches Maximum ingle Shear Strength: 0.690 Pounds Per Square Inch lominal Thread Diameter: 0.190 Inches 0.625 Inches Nominal thread Quantity Per Inch: 120 Inches Infinimum Tensile Strength: 160000 Pounds Per Square Inch Idardness Rating: 160000 Pounds Per Square Inch Idardness Rati	Head Style:	Hexagon
Inip Diameter: 0.1889 Inches Minimum And 0.1894 Inches Maximum 2690 Pounds Per Square Inch 2690 Pounds Per Square Inch 2690 Inches 2690 Pounds Per Square Inch 2690 Inches 2690 Pounds Per Square Inch 2690 Inches 2690 Inches 2690 Pounds Per Square Inch 2690 Inches 2690 Pounds Per Square Inch 2690 Inches 2790 Inches 2890 Inches Nominal 2890 Inches Nomi	Head Height:	0.078 Inches Minimum And 0.110 Inches Maximum
ingle Shear Strength: 2690 Pounds Per Square Inch Jominal Thread Diameter: 0.190 Inches Jorip Length: 0.625 Inches Nominal Jorip Length: 0.625 Inches Nominal Jorip Length: 160000 Pounds Per Square Inch Jorinimum Tensile Strength: 160000 Pounds Per Jorinimum Tensile Strength: 160000 Pou	Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Indianal Thread Diameter: In plant	Grip Diameter:	0.1889 Inches Minimum And 0.1894 Inches Maximum
Inip Length: O.625 Inches Nominal O.625 In	Single Shear Strength:	2690 Pounds Per Square Inch
Thread Quantity Per Inch: Inimium Tensile Strength: Inimium Tensile S	Nominal Thread Diameter:	0.190 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-	Grip Length:	0.625 Inches Nominal
Alardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Alassification: Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Material Document And Cadmium Threads And Chromate Head Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Material Document And Cadmium Head And Chromate Head Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Material Document And Cadmium Threads And Chromate Head Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Material Document And Cadmium Threads Material Document And Cadmium Threads Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Material Document And Cadmium Threads Material Document And Cadmium Threads Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Material Document And Cadmium Threads Material Document And Cadmium Threads Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads	Thread Quantity Per Inch:	32
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Re	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Atterial Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall furface Treatment: Cadmium Threads And Chromate Threads Cadmium Head And Chromate Head Classification: Curface Treatment Document And Classification: Curface Treatment Document And Classification: Chread Series Designator: Unjf Unjf Unjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Mil Spe	Material:	
turface Treatment: Cadmium Threads And Chromate Threads Curface Treatment: Cadmium Head And Chromate Head Curface Treatment Document And Classification: Curface Treatment Document And Curface Treatment Responses Head Curface Treatment Document And Curface Treatment Document Responses Threads Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Document And Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Document Responses Head Curface Treatment Document And Curface Treatment Docum	Material Document And	
Surface Treatment: Cadmium Head And Chromate Head Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Head Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Classification: Chread Series Designator: Unjf	Classification:	Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
turface Treatment Document And Classification: Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Head Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Classification: Chread Series Designator: Unjf	Surface Treatment:	Cadmium Threads And Chromate Threads
Classification: Ourface Treatment Document And Classification: Classification: Chread Series Designator: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Head Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads Unjf Unjf	Surface Treatment:	Cadmium Head And Chromate Head
Classification: Chread Series Designator: Unjf Chread Series Designator: Class 3 Fed Spec All Treatment Responses Threads	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Head
·	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads
pecification/standard Data: 80205-nas464 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas464 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS464-3A10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS464-3A10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS464-3A10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS464-3A10 and selecting the quantity you want then click "add to cart".