

## P/N NAS464-3A10

### **Description**

Fastener Length: 0-63/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS4643A10

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-285-7528

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS464-3A10 Specifications

Three d Class.	2-
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.327 Inches Minimum And 0.374 Inches Maximum
Fastener Length:	0.953 Inches Minimum And 1.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.078 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Grip Diameter:	0.1889 Inches Minimum And 0.1894 Inches Maximum
Single Shear Strength:	2690 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.625 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Threads And Chromate Threads
Surface Treatment:	Cadmium Head And Chromate Head
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Head
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Threads
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas464 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory onlin "add to cart". Once items are in your ca			<u>e+bolts/NAS464-3A10</u> and s	selecting the quantity you	want then click
, , , , , , , , , , , , , , , , , , , ,	,	,			
	Prov	vided by <u>Military-Fasteners</u>	s.com		