

P/N NAS464-4-15

Description

Fastener Length: 1-1/4", Thread: 1/4-28, Thread Length: 5/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS464415

Minimum Qty (MOQ): 5

NSN: 5306-00-639-2302

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS464-4-15 Specifications

Thread Length: 0.343 Inches Minimum Fastener Length: 1.281 Inches Nominal Head Style: Hexagon Head Height: 0.125 Inches Nominal Wildth Between Flats: 0.438 Inches Nominal Grip Diameter: 0.2492 Inches Nominal Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Single Shear Strength: 0.580 Inches Mominal Thread Diameter: 0.938 Inches Nominal Grip Length: 0.938 Inches Nominal Hardness Rating: 0.938 Inches Nominal Unstract From Head Largest 160000 Pounds Per Square Inch Hardness Rating: 0.900 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest 1.26 Inches Nominal First Hole Center: 3.126 Inches Nominal First Hole Center: 4.26 Inches Nominal First Hole Material Document And Overall Or Steel Comp 4037 Overall Mills-5626 Mil Spec 1st Material Response Overall Or Mills-5000 Mill Spec 2nd Material Response Overall Or Mills-6049 Mill Spec 5th Material Response Overall Or Mills-6049 Mill Spec 5th Material Response Overall Or Mills-6049 Mill Spec 5th Material Response Overall Or Mills-604	Thread Class:	3a
Thread Length: 0.343 Inches Minimum Fastener Length: 1.281 Inches Nominal Head Style: Hexagon Head Height: 0.125 Inches Nominal Width Between Flats: 0.438 Inches Nominal Width Between Flats: 0.438 Inches Nominal Grip Diameter: 0.2492 Inches Nominal Shank Unthreaded Hole Diameter: 0.76 Inches Nominal First Hole Slingle Shear Strength: 0.250 Inches Nominal First Hole Slingle Shear Strength: 0.295 Inches Nominal Minimum Tensile Strength: 0.938 Inches Nominal Hinmum Tensile Strength: 1.6000 Pounds Per Square Inch Mardiness Rating: 0.500 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.126 Inches Nominal First Hole Waterial: 2.126 Inches Nominal First Hole Waterial: 2.126 Inches Nominal First Hole Waterial Document And Classification: 2.126 Inches Material Response Overall Or Mils-6098 Mil Spec 1st Material Response Overall Or Mils-6098 Mil Spec 3rd Material Response Overall Or Mils-6098 Mil Spec 5th Material Response Overall Or Mils-6098 Mils Spec 5th Material Resp		
Fastener Length: 1.281 Inches Nominal Head Style: Hexagon Head Height: 0.125 Inches Nominal Wildth Between Flats: 0.438 Inches Nominal Grip Diameter: 0.2492 Inches Nominal Shank Unthreaded Hole Diameter: 0.2490 Pounds Per Square Inch Nominal Thread Diameter: 0.250 Inches Grip Length: 0.938 Inches Nominal Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest 1.26 Inches Nominal First Hole Bearing Surface To Shank Hole 1.26 Inches Nominal First Hole Center: 1.26 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Milis-5626 Mil Spec 1st Material Response Overall Or Milis-5098 Mil Spec 2nd Material Response Overall Or Milis-6049 Mil Spec 5th Material Response Overall Or Milis-6098 Mil Spec 4th Material Response Overall Or Milis-6049 Mil Spec 5th Material Response Overall Or Milis-6098 Mil Spec 4th Material Response Overall Or Milis-6049 Mil Spec 5th Material Response Overall O		
Head Style: Hexagon Head Height: 0.125 Inches Nominal Width Between Flats: 0.438 Inches Nominal Grip Diameter: 0.2492 Inches Nominal Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Single Shear Strength: 4650 Pounds Per Square Inch Nominal Thread Diameter: 0.250 Inches Grip Length: 0.938 Inches Nominal Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest 512 Steel Comp 14140 Overall Or Mili-s-6039 Mil Spec 3rd Material Response Overall Or Mili-s-8695 Mil Spec 1st Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-8695 Mil Spec 6th Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6049 Mili Spec 5th Material Response Overall Or Mili-s		
Head Height: 0.125 Inches Nominal Wildth Between Flats: 0.438 Inches Nominal Grip Diameter: 0.2492 Inches Nominal Shank Unthreaded Hole Diameter: 0.250 Inches Nominal First Hole Single Shear Strength: 4650 Pounds Per Square Inch Nominal Thread Diameter: 0.250 Inches Grip Length: 0.938 Inches Nominal Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.126 Inches Nominal First Hole Center: 4.126 Inches Nominal First Hole Center: 5.126 Inches Nominal First Hole Center: 4.126 Inches Nominal First Hole Center: 5.126 Inches Nominal First Hole Center: 6.1276 Comp 4.140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6.150 Overall Or Steel Comp 8.735 Overall Or Steel Comp 8.740 Overall Or Steel Comp 4.037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-803 Mil Spec 3rd Material Document And Classification: 4.269 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Mate		
Width Between Flats: 0.438 Inches Nominal O.2492 Inches Nominal First Hole O.076 Inches O.07		
Grip Diameter: 0.2492 Inches Nominal Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Single Shear Strength: 4650 Pounds Per Square Inch Nominal Thread Diameter: 0.250 Inches Grip Length: 0.938 Inches Nominal Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole center: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-6526 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8693 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec Sth Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec	_	
Shank Unthreaded Hole Diameter: Single Shear Strength: 4650 Pounds Per Square Inch Nominal Thread Diameter: 0.250 Inches Grip Length: 0.938 Inches Nominal Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Mils-s-6059 Mil Spec 1st Material Response Overall Or Mils-s-6009 Mil Spec 2nd Material Response Overall Or Mils-s-8503 Mil Spec 3rd Material Document And Classification: Mirace Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Oq-p-416.ty 2.cl 3 Fed Spec All Treatment Responses Threads		
Single Shear Strength:4550 Pounds Per Square InchNominal Thread Diameter:0.250 InchesGrip Length:0.938 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:\$teel Comp 4140 Overall Or Steel Comp £4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial:\$teel Comp 4140 Overall Or Steel Comp £4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-8603 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Sp		
Nominal Thread Diameter: 0.250 Inches 0.938 Inches Nominal Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8050 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 6th Material Response Overall Or Mil-s-6		
Grip Length: 0.938 Inches Nominal Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec	Single Shear Strength:	4650 Pounds Per Square Inch
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th M	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.126 Inches Nominal First Hole Center: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Wil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-805 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-60	Grip Length:	0.938 Inches Nominal
Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Document And Classification: Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Surface Treatment: Cadmium Threads And Chromate Head Surface Treatment Document And Classification: Surface Treatment Place Comp 4040 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2n	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overa	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Distance From Head Largest Bearing Surface To Shank Hole Center:	1.126 Inches Nominal First Hole
Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Material:	
Surface Treatment Document And Classification: Cadmium Head And Chromate Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Classification:		Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Surface Treatment:	Cadmium Threads And Chromate Threads
Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads	Surface Treatment:	Cadmium Head And Chromate Head
Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads
Thread Series Designator: Unf		Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head
	Thread Series Designator:	Unf

How to Order Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS464-4-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.