

Description

Fastener Length: 1-11/32", Thread: 1/4-28, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS464416
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-508-6788
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS464-4-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Nominal
Fastener Length:	1.344 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Grip Diameter:	0.249 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.000 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Material Document And Classification:	Ams6322 Assn Std 1st Material Response Overall Or Mil-s-6049 Mil Spec 1st Material Response Overall Or Ams6382 Assn Std 2nd Material Response Overall Or Ams6415 Assn Std 3rd Material Response Overall Or Mil-s-5000 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Head
Surface Treatment Document And Classification:	Qq-p-416, Ty II, Cl 2 Fed Spec Single Treatment Response Head
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464-4-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.