

P/N NAS464-4-5

Military-Fasteners.com

Description

Fastener Length: 5/8", Thread: 1/4-28, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS46445
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-639-2532
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS464-4-5 Specifications

Thread Class:3aThread Class:Right-hadThread Length:0.544 Inches MinimumFaster Length:0.556 Inches NominalHead Style:NominalHead Height:0.125 Inches NominalWidth Between Flats:0.438 Inches NominalOldth Between Flats:0.438 Inches NominalShak Unthreaded Hole Diameter:0.2492 Inches Nominal First HoleShak Unthreaded Hole Diameter:0.500 Inches Nominal First HoleOrip Length:0.500 Inches Nominal First HoleNominal Thread Diameter:0.500 Inches Nominal First HoleOrip Length:0.312 Inches NominalThread Quantity Per Inch:28000 Pounds Per Square InchIntread Olameter:0.500 Inches Nominal First HoleDistance Forn Head Larget0.500 Inches Nominal First HoleCarget To Shank Hole0.500 Inches Nominal First HoleSurface To Shank Hole0.500 Inches Nominal First HoleSurface To Shank HoleSocial Or Steel Comp E1340 Overall Or Steel Comp E1350 Overall Or Steel Comp E1350 Overall Or Mil-56039 Mil Spec 5th Material Response Overall Or Mil-56039 Mil Spec 5th Material Response Overall Or Mil-56049 Mil Spec 5th Material Response Overall Or Mil-560		
Thread Length:0.344 Inches MinimumFaster Length:0.556 Inches NominalHead Style:0.125 Inches NominalHead Height:0.125 Inches NominalWidth Between Flats:0.438 Inches NominalOrtpollameter:0.438 Inches NominalShank Unthreaded Hole Diameter:0.409 Inches NominalShank Unthreaded Hole Diameter:0.500 Inches Nominal First HoleNominal Thread Diameter:0.500 Inches NominalOrtpollameter:0.500 Inches NominalNominal Thread Diameter:0.500 Inches NominalOrtpollameter:0.500 Inches NominalThread Quantity Per Inch0.500 Inches NominalMinimum Tensile Strength:0.6000 Pounds Per Square InchBradense Rating:0.500 Inches Nominal Ad.0.0 Rockwell C Maximum OverallBradense Rating:0.500 Inches Nominal First HoleBradense Rating:0.500 Inches Nominal First HoleBradense Rating:0.500 Inches Nominal First HoleCharler:0.500 Inches Nominal First HoleCharler:0.500 Inches Nominal First HoleBradense Rating:0.500 Inches Nominal First HoleCharler:0.500 Inches Nominal Response Overall Or Mile-5000 Mil Spec Ord Material Response Overall Or Mile-5000 Mil Spec Ord Materi		
Pastener Length:0.556 Inches NominalHead Style:HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.2492 Inches NominalGrip Diameter:0.2492 Inches NominalShank Unthreaded Hole Diameter:0.076 Inches Nominal First HoleShank Unthreaded Theight:0.076 Inches Nominal First HoleShank Unthreaded Theight:0.056 Inches Nominal First HoleShank Unthread Diameter:0.026 Inches NominalGrip Length:0.312 Inches NominalHardens Rating:0.312 Inches NominalBistance From Head Largest Bearing Surface To Shank Hole0.500 Inches Nominal First HoleShank Internation:Solo Inches Nominal First HoleMaterial Response Overall On Steel Comp Ed340 Overall On Steel Comp 150 Overall On Steel Comp B735 Overall On Steel Comp A700 Overall On Steel Comp G130 Overall On Steel Comp A700 Overall On Steel Comp G130 Overall On Steel Co		Right-hand
Head Style:HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.438 Inches NominalGrip Diameter:0.2492 Inches Nominal First HoleShank Unthreaded Hol Diamete:0.706 Inches Nominal First HoleSingle Shear Strength:4650 Pounds Per Square InchNominal Thread Diameter:0.250 InchesGrip Length:0.312 Inches NominalThread Quantity Per Inch6000 Pounds Per Square InchHardness Rating:6.000 Pounds Per Square InchHardness Rating:6.000 Pounds Per Square InchBardness Rating:6.000 Pounds Per Square InchBardness Rating:6.000 Pounds Per Square InchHardness Rating:6.000 Pounds Per Square InchBardness Rating:6.000 Pounds Per Square InchBardness Rating:6.000 Pounds Per Square InchNaterial:Scol Inches Nominal First HoleVieral Or Steel Comp 4030 Overall Or Steel Comp E340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4030 OverallMaterial Bocument And Classification:Mil-s-5626 Mill Spec 1st Material Response Overall Or Mil-s-6009 Mill Spec 4th Material Response Overall Or Mil-s-6098 Mill Spec 4th Material Response Overall Or Mill-s-6098 Mill Spec 4th Material Response Overall	Thread Length:	0.344 Inches Minimum
Head Height:0.125 Inches NominalWichts Between Flats:0.438 Inches NominalGrip Diameter:0.2492 Inches Nominal First HoleShank Unthreaded Hole Diamet0.705 Inches Nominal First HoleShank Unthreaded Jameter:0.250 Inches Nominal First HoleNominal Thread Diameter:0.250 Inches Nominal First HoleRef Length:0.312 Inches Nominal First HoleMinimu Tensile Strength:0.302 Inches Nominal First HoleBioles Part Hole0.302 Inches Nominal First HoleHardes Rating:0.302 Inches Nominal First HoleBioles Part Hole0.3000 Pounds Per Square InchHardes Rating:0.300 Inches Nominal First HoleBioles Part Hole0.300 Pounds Per Square InchHardes Rating:0.300 Inches Nominal First HoleBioles Part Hole0.300 Pounds Per Square InchHardes Rating:0.300 Inches Nominal First HoleBioles Part Hole0.300 Pounds Per Square InchMaterial Scione Math Jack ScienceScience From Head Largest Biolos Part HoleBiarder From Head Largest Biardes Science From Head Largest Biolos Part HoleScience From Head Largest Biolos Part HoleBiarder Hole Science From Head Largest Biardes Science Fro	Fastener Length:	0.656 Inches Nominal
Width Between Flats:0.438 Inches NominalGrip Diameter:0.2492 Inches Nominal First HoleShank Unthreadel Hole Diameter:0.076 Inches Nominal First HoleSingle Shear Strength:4650 Pounds Per Square InchNominal Thread Diameter:0.250 InchesGrip Length:0.312 Inches NominalThread Quantity Per Inch:8Bearing Surface Treatment Regions6.000 Pounds Per Square InchHardenss Rating:0.600 Pounds Per Square InchBearing Surface To Shank Hole Center:0.500 Inches Nominal First HoleDistance From Head Largest Bearing Surface To Shank Hole Center:0.500 Inches Nominal First HoleMaterial Document And Classification:Shee Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp B150 Overall Or Steel Comp 8735 Overall Or Mil-s-6098 Mil Spec Ath Material Response Overall	Head Style:	Hexagon
Grip Diameter:0.2492 Inches Nominal First HoleShank Unthreaded Hole Diameter:0.076 Inches Nominal First HoleSingle Shear Strength:4560 Pounds Per Square InchNominal Thread Diameter:0.250 InchesGrip Length:0.312 Inches NominalThread Quantity Per Inch:8Minimu Tensile Strength:160000 Pounds Per Square InchHardness Rating:6.06 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHardness Rating:6.00 Pounds Per Square InchHardness Rating:6.00 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHardness Rating:6.00 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:6.00 Inches Nominal First HoleMaterial:Scole Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp E150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Mil-s-6038 Mil Spec 1st Material Response Overall Or Mil-s-6039 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 1st Material Response Overall Or Mil-s-6039 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 1st Material Response Overall Or Mil-s-6039 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 1st Material Response Overall Or Mil-s-6039 Mil Spec 1st Material Response Overall Or Mil-s-6039 Mil Spec 1st Material Response Overall Or Mil-s-6039 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil S	Head Height:	0.125 Inches Nominal
Shank Unthreaded Hole Diameter:0.076 Inches Nominal First HoleSingle Shear Strength:4550 Pounds Per Square InchNominal Thread Diameter:0.250 InchesOrtje Length:0.312 Inches NominalThread Quantity Per Inch:8Bioloo Pounds Per Square Inch160000 Pounds Per Square InchHardness Rating:30.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallThread Quantity Per Inch:50.0 Inches Nominal First HoleBistance From Head Largest Bearing Surface To Shank HoleSolo Inches Nominal First HoleDistance From Head Largest Bearing Surface To Shank HoleSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8730 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Steel Comp 4140 Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil	Width Between Flats:	0.438 Inches Nominal
Single Shear Strength:4650 Pounds Per Square InchNominal Thread Diameter:0.250 InchesGrip Length:0.312 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.60 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest0.500 Inches Nominal First HoleCenter:0.500 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8037 OverallMaterial:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Mead <tr< td=""><td>Grip Diameter:</td><td>0.2492 Inches Nominal</td></tr<>	Grip Diameter:	0.2492 Inches Nominal
Nominal Thread Diameter:0.250 InchesGrip Length:0.312 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole0.500 Inches Nominal First HoleOurce In Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 7000Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8700Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8700Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or	Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Grip Length:0.312 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole.500 Inches Nominal First HoleObserver IncentionSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Q-p-416.type 2.class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Q-p-416.type 2.class 3 Fed Spec Single Treatment Response Threads	Single Shear Strength:	4650 Pounds Per Square Inch
Thread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:0.500 Inches Nominal First HoleMaterial:0.500 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8730 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Materi	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole0.500 Inches Nominal First HoleOwerall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:q-p-416,type 2,class 3 Fed Spec Single Treatment Response ThreadsSurface Treatment Document And Classification:q-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Grip Length:	0.312 Inches Nominal
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:	Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole0.500 Inches Nominal First HoleMaterial:0.500 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment:Cadmium HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center:0:500 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8736 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:op-9416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:op-9416,type 2,class 3 Fed Spec Single Treatment Response Threads	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Bearing Surface To Shank Hole	0.500 Inches Nominal First Hole
Material Document And Classification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium ThreadsSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Material:	
Surface Treatment:Cadmium HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response HeadSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads		Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or
Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Head Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Surface Treatment:	Cadmium Threads
Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Head Surface Treatment Document And Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads	Surface Treatment:	Cadmium Head
Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads		Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Head
Thread Series Designator: Unf		Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Threads
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS464-4-5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.