

# **P/N NAS464-4-7**

## **Description**

Fastener Length: 3/4", Thread: 1/4-28, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

### **Additional Information**

SKU / Model:	NAS46447
Minimum Qty (MOQ):	5
NSN:	5306-00-639-2769
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS464-4-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.343 Inches Minimum
Fastener Length:	0.781 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.438 Inches Nominal
Grip Diameter:	0.2492 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Nominal First Hole
Single Shear Strength:	4650 Pounds Per Square Inch
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.438 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.626 Inches Nominal First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Threads And Chromate Threads
Surface Treatment:	Cadmium Head And Chromate Head
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head
Thread Series Designator:	Unf

# Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS464-4-7">https://military-fasteners.com/bolts/machine+bolts/NAS464-4-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS464-4-7">https://military-fasteners.com/bolts/machine+bolts/NAS464-4-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/NAS464-4-7">https://military-fasteners.com/bolts/machine+bolts/NAS464-4-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/NAS464-4-7">https://military-fasteners.com/bolts/machine+bolts/NAS464-4-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/NAS464-4-7">https://military-fasteners.com/bolts/NAS464-4-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/NAS464-4-7">https://military-fasteners.com/bolts/NAS464-4-7</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/NAS464-4-7">https://military-fasteners.com/bolts/NAS464-4-7</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/NAS464-4-7">https://military-fasteners.com/bolts/NAS464-4-7</a> and selecting the properties of the properties o