

P/N NAS464-6-14

Description

Fastener Length: 1-1/4", Thread: 3/8-24, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

 SKU / Model:
 NAS464614

 Minimum Qty (MOQ):
 5 EA

 NSN:
 5306-00-282-4860

 Schedule B:
 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS464-6-14 Specifications

Thread Direction: Sight-hand Cassification: Sight-hand Cassification: Sight-hand Cassification: Sight-hand Cassification: Sight-hand Cassification: Surface Treatment Document And Cassification: Surface Treatment Surf	-1 10	
Thread Length: 0.343 Inches Minimum And 0.390 Inches Maximum Fasteer Length: 1.218 Inches Minimum And 1.265 Inches Maximum Head Style: Hexagon Head Height: 0.188 Inches Nominal Width Between Flats: 0.552 Inches Minimum And 0.3742 Inches Maximum Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 0.1050 Inches Nominal First Hole Single Shear Strength: 0.500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole 0.94 Inches Nominal First Hole Center 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mairial Response Overall Or Milis-5008 Mil Spec 2nd Material Response Overall Or Milis-8093 Mil Spec 3th Material Response Overall Or Milis-8693 Mil Spec 5th Material Response Overall Or Milis-8695 Mil Spec 5th Material Response Overall Or Milis-8695 Mil Spec 5th Material Response Overall Or Milis-8693 Mil Spec 5th Material Response Overall Or Milis-8695 Mil	Thread Class:	3a
Fastener Length: 1.218 Inches Minimum And 1.265 Inches Maximum Head Style: Hexagon Head Height: 0.158 Inches Minimum And 0.564 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.3742 Inches Maximum Grip Dlameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Dlameter: 0.06 Inches Nominal First Hole Single Shear Strength: 1.050 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Oning Spear Strength: 0.875 Inches Nominal Hardness Rating: 0.875 Inches Nominal Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.094 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp £4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mils-5626 Mil Spec 1st Material Response Overall Or Mils-5098 Mil Spec 2nd Material Response Overall Or Mils-8503 Mil Spec 5th Material Response Overall Or Mils-8698 Mil Spec 3th Material Response Overall Or Mils-8503 Mil Spec 5th Material Response Overall Or Mils-8698 Mil Spec 5th Material Response Overall Or Mils-8503 Mil Spec 5th Material Response Overall Or Mils-8698 Mil Spec 5th Material Response Overall Or Mils	Thread Direction:	Right-hand
Head Style: Hexagon Head Height: 0.188 Inches Nominal Width Between Flats: 0.552 Inches Minimum And 0.3742 Inches Maximum Grip Diametre: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 0.355 Inches Grip Length: 0.375 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch. 24 Minimum Tensile Strength: 60000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.094 Inches Nominal First Hole Material: 2.094 Inches Nominal First Hole Material Document And Classification: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec dth Material Respons	Thread Length:	0.343 Inches Minimum And 0.390 Inches Maximum
Head Height: 0.188 Inches Nominal Width Between Flats: 0.552 Inches Minimum And 0.3742 Inches Maximum Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hob Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 0.375 Inches Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 2 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole 1.094 Inches Nominal First Hole Center: 1.094 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp £4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp £407 Overall Or Mil-s-5605 Mil Spec 3rd Material Response Overall Or Mil-s-5608 Mil Spec 4th Material Response Overall Or Mil-s-8093 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-8	Fastener Length:	1.218 Inches Minimum And 1.265 Inches Maximum
Width Between Flats: 0.552 Inches Minimum And 0.564 Inches Maximum Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 10500 Pounds Per Square Inch Mominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 2 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Bearing Surface To Shank Hole Center: 2.094 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Becomment And Classification: Mill-s-6626 Mill Spec 1st Material Response Overall Or Mill-s-6098 Mill Spec 4th Material Response Overall Or Mill-s-8503 Mill Spec 5th Material Response Overall Or Mill-s-8503 Mi	Head Style:	Hexagon
Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 10500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 3.094 Inches Nominal First Hole Center: 3.094 Inches Nominal First Hole Material: 3.094 Inches Nominal First Hole Waterial: 3.094 Inches Nominal First Hole <t< th=""><th>Head Height:</th><th>0.188 Inches Nominal</th></t<>	Head Height:	0.188 Inches Nominal
Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 10500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 3rd Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Plead	Width Between Flats:	0.552 Inches Minimum And 0.564 Inches Maximum
Single Shear Strength:10500 Pounds Per Square InchNominal Thread Diameter:0.375 InchesGrip Length:0.875 Inches NominalThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4047 OverallMaterial Document And Classification:Mil-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface TreatmentCadmium Threads And Chromate ThreadsSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses ThreadsSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads	Grip Diameter:	0.3737 Inches Minimum And 0.3742 Inches Maximum
Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.094 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8030 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mil-s-8030 Mil Spec 5th Mate	Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.094 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Qrp-416.ty 2.cl 3 Fed Spec All Treatment Responses Threads Surface Treatment Document And Classification: Qrp-416,ty 2.cl 3 Fed Spec All Treatment Responses Head	Single Shear Strength:	10500 Pounds Per Square Inch
Thread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.094 Inches Nominal First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec Mil	Nominal Thread Diameter:	0.375 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Document And Classification: Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Classification:	Grip Length:	0.875 Inches Nominal
Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Document And Classification: Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Surface Treatment Document And Classification: Surface Treatment Document And Classification: Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overa	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Bearing Surface To Shank Hole	1.094 Inches Nominal First Hole
Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Material:	·
Surface Treatment: Surface Treatment Document And Classification: Cadmium Head And Chromate Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Classification:		Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or
Surface Treatment Document And Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Surface Treatment:	Cadmium Threads And Chromate Threads
Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Surface Treatment:	Cadmium Head And Chromate Head
Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head		Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads
Thread Series Designator: Unf		Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head
	Thread Series Designator:	Unf

How to Order Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS464-6-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order. Provided by Military-Fasteners.com