

**Description**

Fastener Length: 1-29/64", Thread: 3/8-24, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS464617
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-297-7937
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

# P/N NAS464-6-17 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.344 Inches Minimum And 0.391 Inches Maximum
<b>Fastener Length:</b>	1.406 Inches Minimum And 1.453 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.188 Inches Nominal
<b>Width Between Flats:</b>	0.552 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.3737 Inches Minimum And 0.3742 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Nominal First Hole
<b>Single Shear Strength:</b>	10500 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.062 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.281 Inches Nominal First Hole
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Threads And Chromate Threads
<b>Surface Treatment:</b>	Cadmium Head And Chromate Head
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464-6-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.