

P/N NAS464-6-25

Description

Fastener Length: 1-61/64", Thread: 3/8-24, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS464625

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-292-6453

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS464-6-25 Specifications

Thread Length: 0.344 Inches Minimum And 0.391 Inches Maximum Fastener Length: 1.906 Inches Minimum And 1.953 Inches Maximum Head Style: Hexagon Head Height: 0.188 Inches Nominal Width Between Flats: 0.552 Inches Minimum And 0.564 Inches Maximum Grip Dlameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Grip Dlameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Grip Dlameter: 0.3755 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Dlameter: 0.106 Inches Nominal First Hole Single Shear Strength: 0.5502 Inches Nominal First Hole Grip Length: 1.562 Inches Nominal First Hole Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 1.5602 Inches Nominal Bracker Forn Head Larges Bearing Surface To Shank Hole Center: 25 Bataria Surface To Shank Hole Center: 35 Bataria Strength: 25 Bataria Document And Mili-s-5026 Mil Spec 13t Material Response Overall Or Mili-s-5030 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 2rd Material Document And Classification: 36 Surface Treatment: 26 Surface Treatment Document And Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Classification: 30 Surface Treatment Document And Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Classification: 30 Surface Treatment Document And Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Classification: 30 Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads	Thursd Class	
Thread Length: 0.344 Inches Minimum And 0.391 Inches Maximum Faster Length: 1.906 Inches Minimum And 1.953 Inches Maximum Head Style: Hexagon Head Height: 0.188 Inches Nominal Width Between Flats: 0.552 Inches Minimum And 0.364 Inches Maximum Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 10500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest 1.781 Inches Nominal First Hole Bearing Surface To Shank Hole 2.781 Inches Nominal First Hole Center: 2.781 Inches Nominal First Hole Material Document And Classification: Seel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-8098 Mil Spec 3rd Material Response Overall Or Mil-s-8098 Mil Spec 4th Material Response Overall Or Mi	Thread Class:	3a
Fastener Length: 1,906 Inches Minimum And 1,953 Inches Maximum Head Style: Hexagon Head Height: 0.158 Inches Nominal Width Between Flats: 0.552 Inches Minimum And 0.3742 Inches Maximum Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 10500 Pounds Per Square Inch Mominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1,781 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6750 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mili-s-5000 Mil Spec 2nd Material Response Overall Or Mili-s-803 Mil Spec 5th Material Response Overall Or Mili-s-8098 Mil Spec 4th Material Response Overall Or Mili-s-8503 Mil Spec 5th Material Response Overall Or Mili-s-6098 Mil Spec 6th Material Response Overall Or Mili-s-8098 Mil Spec 5th Mater		
Head Style: Hexagon Head Helght: 0.188 Inches Nominal Width Between Flats: 0.552 Inches Minimum And 0.564 Inches Maximum Grip Dlameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Dlameter: 0.106 Inches Nominal First Hole Single Shear Strength: 0.500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 51.781 Inches Nominal First Hole Center: 51.7	Thread Length:	0.344 Inches Minimum And 0.391 Inches Maximum
Head Height: 0.188 Inches Nominal Width Between Flats: 0.552 Inches Minimum And 0.564 Inches Maximum Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 1.056 Inches Nominal First Hole Single Shear Strength: 1.050 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 2 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest 1.781 Inches Nominal First Hole Bearing Surface To Shank Hole 1.781 Inches Nominal First Hole Center: 1.781 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Or Mil-s-5626 Mil Spec 3th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8693 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Respo	Fastener Length:	1.906 Inches Minimum And 1.953 Inches Maximum
Width Between Flats: 0.552 Inches Minimum And 0.564 Inches Maximum Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 0.500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.781 Inches Nominal First Hole Center: 3.842 Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mil-s-8009 Mil Spec 4th Material Response Overall Or Mil-s-8034 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 4th Material Response Overall Or Mil-s-8098 Mil Spec 4th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 4th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 4th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Res	Head Style:	Hexagon
Grip Diameter: 0.3737 Inches Minimum And 0.3742 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 10500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 3.781 Inches Nominal First Hole Material: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mills-5626 Mill Spec 1st Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-6049 Mil Spec 3rd Material Response Overall Or Mils-6098 Mil Spec 4th Material Response Overall Or Mils-8503 Mil Spec 5th Material Response Overall Or Mils-8695 Mil Spec 6th Material Response Overall Or Mils-8695 Mil Spec 5th Material Response Overall Or Mils-8695 Mils Spec	Head Height:	0.188 Inches Nominal
Shank Unthreaded Hole Diameter: 0.106 Inches Nominal First Hole Single Shear Strength: 0.500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 35.2 Ecel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Overall Or Miles-6098 Mil Spec 2nd Material Response Overall Or Miles-6049 Mil Spec 3rd Material Response Overall Or Miles-8098 Mil Spec 4th Material Response Overall Or Miles-8590 Mil Spec 3rd Material Response Overall Or Miles-8590 Mil Spec Overall Or Miles-8699 Mil Spec 4th Material Response Overall Or Miles-8590 Miles Spec Miles Material Response Overall Or Miles-8590 Miles Spec Miles Material Response Overall Or Miles-8590 Miles-8695 Miles Spec Miles Material Response Overall Or Miles-8690 Miles Spec Miles Material Response Overall Or Miles-8500 Miles Spec Miles Material Response Overall Or Miles-8604 Miles-86	Width Between Flats:	0.552 Inches Minimum And 0.564 Inches Maximum
Single Shear Strength: 10500 Pounds Per Square Inch Nominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6695 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6695 Mil Spec 2nd Material Response Overall Or Mil-s-8695 Mil Spec Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec Spec All Treatment Responses Threads Surface Treatment Document And Classification: Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Surface Treatment Document And Classification: Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Grip Diameter:	0.3737 Inches Minimum And 0.3742 Inches Maximum
Nominal Thread Diameter: 0.375 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 352 Material Document And Classification: 363 Surface Treatment Document And Classification: 364 Surface Treatment Document And Classification: 364 Surface Treatment Document And Classification: 365 Surface Tr	Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.781 Inches Nominal First Hole Center: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-8095 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mil-s-8098 Mil Spec 5th Material Response Overall Or Mi	Single Shear Strength:	10500 Pounds Per Square Inch
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Naterial: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Nominal Thread Diameter:	0.375 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material: Material Document And Classification: Surface Treatment: Cadmium Threads And Chromate Head Cadmium Head And Chromate Head Classification: Surface Treatment Document And Classification: Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Classification: Material Document And Classification: Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Grip Length:	1.562 Inches Nominal
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.781 Inches Nominal First Hole Center: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Surface Treatment: Cadmium Threads And Chromate Head Surface Treatment Document And Classification:	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8503 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overa	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Threads And Chromate Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Bearing Surface To Shank Hole	1.781 Inches Nominal First Hole
Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 4th Material Response Overall Or Mil Spec 4th Mate	Material:	
Surface Treatment Document And Classification: Cadmium Head And Chromate Head Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Classification:	Material Document And Classification:	Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Surface Treatment:	Cadmium Threads And Chromate Threads
Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head	Surface Treatment:	Cadmium Head And Chromate Head
Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head		Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Threads
Thread Series Designator: Unf		Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Head
	Thread Series Designator:	Unf

How to Order Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS464-6-25 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order. Provided by Military-Fasteners.com