

Description

Fastener Length: 2-13/32", Thread: 3/4-16, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS464P1229
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-226-3549
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS464P12-29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.541 Inches Minimum And 0.610 Inches Maximum
Fastener Length:	2.369 Inches Minimum And 2.406 Inches Maximum
Head Style:	Hexagon
Head Height:	0.359 Inches Minimum And 0.371 Inches Maximum
Width Between Flats:	1.052 Inches Minimum And 1.065 Inches Maximum
Grip Diameter:	0.7477 Inches Minimum And 0.7488 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Nominal First Hole
Nominal Thread Diameter:	0.750 Inches
Grip Length:	1.796 Inches Minimum And 1.828 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.734 Inches Minimum First Hole And 2.766 Inches Maximum First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas464 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P12-29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.