

Description

Fastener Length: 2-1/2", Thread: 3/4-16, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS464P1231 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-630-8059 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS464P12-31 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.562 Inches Minimum |
| Fastener Length: | 2.500 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.375 Inches Nominal |
| Width Between Flats: | 1.062 Inches Nominal |
| Grip Diameter: | 0.7488 Inches Nominal |
| Shank Unthreaded Hole Diameter: | 0.141 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.750 Inches |
| Grip Length: | 1.938 Inches Nominal |
| Thread Quantity Per Inch: | 16 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.313 Inches Nominal First Hole |
| Material: | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas464 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P12-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.