

# P/N NAS464P12-37

### **Description**

Fastener Length: 2-7/8", Thread: 3/4-16, Thread Length: 9/16

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS464P1237

Minimum Qty (MOQ):

NSN: 5306-00-717-8556

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS464P12-37 Specifications

_, , , ,	
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.563 Inches Minimum
Fastener Length:	2.875 Inches Nominal
Head Style:	Hexagon
Head Height:	0.375 Inches Nominal
Width Between Flats:	1.062 Inches Nominal
Grip Diameter:	0.7488 Inches Nominal
Shank Unthreaded Hole Diameter:	0.141 Inches Nominal First Hole
Single Shear Strength:	41950 Pounds Per Square Inch
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.312 Inches Nominal
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.687 Inches Nominal First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas464 Professional/industrial Association Standard

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS464P12-37">https://military-fasteners.com/bolts/machine+bolts/NAS464P12-37</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.