



★ FASTENERS

Military-Fasteners.com

P/N NAS464P14-76

## Description

Fastener Length: 5-27/64", Thread: 7/8-14, Thread Length: 43/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS464P1476
Minimum Qty (MOQ):	1
NSN:	5306-00-184-9737
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS464P14-76 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.625 Inches Minimum And 0.672 Inches Maximum
<b>Fastener Length:</b>	5.375 Inches Minimum And 5.422 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.422 Inches Minimum And 0.454 Inches Maximum
<b>Width Between Flats:</b>	1.240 Inches Minimum And 1.253 Inches Maximum
<b>Grip Diameter:</b>	0.8725 Inches Minimum And 0.8737 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.141 Inches Nominal First Hole
<b>Nominal Thread Diameter:</b>	0.875 Inches
<b>Grip Length:</b>	4.750 Inches Nominal
<b>Thread Quantity Per Inch:</b>	14
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	5.172 Inches Minimum First Hole And 5.204 Inches Maximum First Hole
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas464 Professional/industrial Association Standard

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P14-76> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.