

**Description**

Fastener Length: 1-15/32", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS464P318
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-551-5590
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

P/N NAS464P3-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Minimum
Fastener Length:	1.469 Inches Nominal
Head Style:	Hexagon
Head Height:	0.094 Inches Nominal
Width Between Flats:	0.375 Inches Nominal
Grip Diameter:	0.1894 Inches Nominal
Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Single Shear Strength:	2690 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.125 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.313 Inches Nominal First Hole
lii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-8503 Mil Spec 5th Material Response Or Mil-s-8695 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,class 3 Fed Spec Single Treatment Response Overall

Thread Series Designator:	Unf
---------------------------	-----

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS464P3-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.