

P/N NAS464P3-20

Military-Fasteners.com

## Description

Bolt part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

## **Additional Information**

SKU / Model:	NAS464P320
Minimum Qty (MOQ):	30 EA
NSN:	5306-00-550-2114
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS464P3-20 Specifications

	3a
read Direction:	Right-hand
read Length:	0.328 Inches Minimum And 0.375 Inches Maximum
stener Length:	1.578 Inches Minimum And 1.625 Inches Maximum
ad Style:	Hexagon
ad Height:	0.094 Inches Nominal
idth Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
ip Diameter:	0.1885 Inches Minimum And 0.1894 Inches Maximum
ank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
ngle Shear Strength:	2690 Pounds Per Square Inch
ominal Thread Diameter:	0.190 Inches
ip Length:	1.250 Inches Nominal
read Quantity Per Inch:	32
nimum Tensile Strength:	160000 Pounds Per Square Inch
rdness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
stance From Head Largest aring Surface To Shank Hole inter:	1.438 Inches Nominal First Hole
aterial:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall
aterial Document And assification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
rface Treatment Document And assification:	Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall
read Series Designator:	Unf

## How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS464P3-20</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.