

P/N NAS464P3-3

Military-Fasteners.com

Description

Fastener Length: 9/16", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS464P33 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-579-4264 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS464P3-3 Specifications

| Thread Class: | За |
|---|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.327 Inches Minimum And 0.374 Inches Maximum |
| Fastener Length: | 0.515 Inches Minimum And 0.562 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.078 Inches Minimum And 0.110 Inches Maximum |
| Width Between Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1894 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Nominal First Hole |
| Single Shear Strength: | 2690 Pounds Per Square Inch |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.188 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.360 Inches Minimum First Hole And 0.392 Inches Maximum First Hole |
| Material: | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas464 Professional/industrial Association Standard |
| | |

How to Order

Order this bolt-shear from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS464P3-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.