



Military-Fasteners.com

**P/N NAS464P3-9**

## Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS464P39
Minimum Qty (MOQ):	25
NSN:	5306-00-551-6985
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NAS464P3-9



\* See page 2 for technical characteristics

## P/N NAS464P3-9 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.328 Inches Minimum And 0.375 Inches Maximum
<b>Fastener Length:</b>	0.890 Inches Minimum And 0.937 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.094 Inches Nominal
<b>Width Between Flats:</b>	0.365 Inches Minimum And 0.377 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1894 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Nominal First Hole
<b>Single Shear Strength:</b>	2690 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.562 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	0.750 Inches Nominal First Hole
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS464P3-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.