

Description

Fastener Length: 1-1/2", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS464P3A18 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-550-3451 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS464P3A18 Specifications

| | |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.328 Inches Minimum And 0.375 Inches Maximum |
| Fastener Length: | 1.453 Inches Minimum And 1.500 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.094 Inches Nominal |
| Width Between Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1894 Inches Maximum |
| Single Shear Strength: | 2690 Pounds Per Square Inch |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.125 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS464P3A18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.