

Description

Fastener Length: 1-9/64", Thread: 1/4-28, Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS464P4A10
Minimum Qty (MOQ):	10
NSN:	5306-01-468-2075
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NAS464P4A10



NAS464P4A10



P/N NAS464P4A10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.953 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.062 Inches Minimum And 1.141 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Grip Diameter:	0.250 Inches Nominal
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.625 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.609 Inches Minimum Overall And 0.641 Inches Maximum Overall
Special Features:	Shank Is Cadmium Plated Per Qq-p-416, Type Ii, Class 2
Material:	Steel Overall
Material Document And Classification:	Nas498 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas464 Professional/Industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P4A10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.