

Description

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS464P4A15 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-608-7899 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS464P4A15 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.3278 Inches Minimum And 0.3748 Inches Maximum |
| Fastener Length: | 1.2653 Inches Minimum And 1.3123 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Nominal |
| Width Between Flats: | 0.428 Inches Minimum And 0.440 Inches Maximum |
| Grip Diameter: | 0.2483 Inches Minimum And 0.2492 Inches Maximum |
| End Item Identification: | A10 |
| Nominal Thread Diameter: | 0.25 Inches |
| Grip Length: | 0.9375 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P4A15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.