

**Description**

Fastener Length: 1-5/32", Thread: 1/4-24, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS464P5A13
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-577-2009
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS464P5A13 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.359 Inches Nominal
<b>Fastener Length:</b>	1.171 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.156 Inches Nominal
<b>Width Between Flats:</b>	0.490 Nominal Mils And 0.502 Nominal Centimeters
<b>Grip Diameter:</b>	0.310 Nominal Mils And 0.311 Nominal Centimeters
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.812 Nominal Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty2 Cl3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P5A13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.