

P/N NAS464P5A23

Description

Fastener Length: 1-13/16", Thread: 1/4-24, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS464P5A23

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-639-2259

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS464P5A23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.327 Inches Minimum And 0.374 Inches Maximum
Fastener Length:	1.765 Inches Minimum And 1.812 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3108 Inches Minimum And 0.3117 Inches Maximum
Single Shear Strength:	7300 Pounds Per Square Inch
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.438 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And	Cadimani Overdii / tild Cili Cili della Cili Cili della Cili Cili Cili della Cili Cili Cili Cili Cili Cili Cili C
Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas464 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS464P5A23 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.