

## **P/N NAS464P5A9**

## **Description**

Fastener Length: 61/64", Thread: 1/4-24, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS464P5A9

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-206-6401

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS464P5A9 Specifications**

| Thread Class:                                  | 3a   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.344 Inches Minimum And 0.391 Inches Maximum  |
| Fastener Length:                               | 0.906 Inches Minimum And 0.953 Inches Maximum  |
| Head Style:                                    | Hexagon  |
| Head Height:                                   | 0.156 Inches Nominal   |
| Width Between Flats:                           | 0.490 Inches Minimum And 0.502 Inches Maximum  |
| Grip Diameter:                                 | 0.3108 Inches Minimum And 0.3117 Inches Maximum  |
| Single Shear Strength:                         | 7300 Pounds Per Square Inch  |
| Nominal Thread Diameter:                       | 0.312 Inches   |
| Grip Length:                                   | 0.562 Inches Nominal   |
| Thread Quantity Per Inch:                      | 24   |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch  |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| Material:                                      | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4037 Overall  |
| Material Document And Classification:          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall  |
| Thread Series Designator:                      | Unf  |

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS464P5A9">https://military-fasteners.com/bolts/machine+bolts/NAS464P5A9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS464P5A9">https://military-fasteners.com/bolts/machine+bolts/NAS464P5A9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS464P5A9">https://military-fasteners.com/bolts/machine+bolts/NAS464P5A9</a> and selecting the quantity you want then click