

P/N NAS464P6A6

Military-Fasteners.com

Description

Fastener Length: 23/32", Thread: 3/8-24, Thread Length: 11/32", NAS464 series bolt

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS464P6A6
Minimum Qty (MOQ):	10
NSN:	5306-00-616-6307
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS464P6A6 Specifications

Thread Class:	3a	
Thread Direction:	Right-hand	
Thread Length:	0.359 Inches Minimum	
Fastener Length:	0.734 Inches Nominal	
Head Style:	Hexagon	
Head Height:	0.188 Inches Nominal	
Width Between Flats:	0.562 Inches Nominal	
Grip Diameter:	0.3742 Inches Nominal	
Single Shear Strength:	10500 Pounds Per Square Inch	
Nominal Thread Diameter:	0.375 Inches	
Grip Length:	0.375 Inches Nominal	
Thread Quantity Per Inch:	24	
Minimum Tensile Strength:	160000 Pounds Per Square Inch	
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall	
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall	
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall	
Surface Treatment:	Cadmium Overall And Chromate Overall	
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	
Thread Series Designator:	Unf	

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS464P6A6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.