

Description

Fastener Length: 1-1/4", Thread: 3/8-24, Thread Length: 3/8", NAS464 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS464P6LA14
Minimum Qty (MOQ):	10
NSN:	5306-00-806-9096
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS464P6LA14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.437 Inches Minimum
Fastener Length:	1.312 Inches Nominal
Head Style:	Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.562 Inches Nominal
Grip Diameter:	0.3742 Inches Nominal
Single Shear Strength:	10500 Pounds Per Square Inch
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.875 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P6LA14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.