



[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS464P6LA16**

## Description

Fastener Length: 1-7/16", Thread: 3/8-24, Thread Length: 7/16", NAS464 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS464P6LA16                              |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-00-801-5343                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS464P6LA16 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.438 Inches Minimum  |
| <b>Fastener Length:</b>                               | 1.438 Inches Nominal  |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.188 Inches Nominal  |
| <b>Width Between Flats:</b>                           | 0.462 Inches Nominal  |
| <b>Grip Diameter:</b>                                 | 0.3742 Inches Nominal   |
| <b>Single Shear Strength:</b>                         | 10500 Pounds Per Square Inch  |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Grip Length:</b>                                   | 1.000 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Material:</b>                                      | Steel Comp 4037 Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall       |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P6LA16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.