

**Description**

Fastener Length: 1-7/16", Thread: 3/8-24, Thread Length: 7/16", NAS464 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS464P6LA16
Minimum Qty (MOQ):	10
NSN:	5306-00-801-5343
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS464P6LA16 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Minimum
<b>Fastener Length:</b>	1.438 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.188 Inches Nominal
<b>Width Between Flats:</b>	0.462 Inches Nominal
<b>Grip Diameter:</b>	0.3742 Inches Nominal
<b>Single Shear Strength:</b>	10500 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.000 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 4037 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P6LA16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.