

Description

Fastener Length: 2-29/32", Thread: 3/8-24, Thread Length: 15/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS464P6LA39 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-543-5724 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS464P6LA39 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.422 Inches Minimum And 0.469 Inches Maximum |
| Fastener Length: | 2.859 Inches Minimum And 2.906 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.172 Inches Minimum And 0.204 Inches Maximum |
| Width Between Flats: | 0.552 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.3733 Inches Minimum And 0.3742 Inches Maximum |
| Single Shear Strength: | 10500 Pounds Per Square Inch |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 2.437 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 2 Cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas464 Professional/industrial Association Standard |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P6LA39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.