

P/N NAS464P7A14

Description

Fastener Length: 1-21/64", Thread: 7/16-20, Thread Length: 29/64", NAS464 series bolt

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS464P7A14

Minimum Qty (MOQ):

NSN: 5306-00-584-5739

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS464P7A14 Specifications

Thread Direction: Right-hand Thread Length: 0.396 Inches Minimum And 0.463 Inches Maximum Fastener Length: 1.281 Inches Minimum And 1.328 Inches Maximum Head Style: Hexagon Head Height: 0.203 Inches Minimum And 0.235 Inches Maximum Width Between Flats: 0.615 Inches Minimum And 0.627 Inches Maximum Grip Diameter: 0.4358 Inches Minimum And 0.4367 Inches Maximum Single Shear Strength: 14300 Pounds Per Square Inch Nominal Thread Diameter: 0.438 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Thread Length: 0.396 Inches Minimum And 0.463 Inches Maximum Fastener Length: 1.281 Inches Minimum And 1.328 Inches Maximum Head Style: Hexagon Head Height: 0.203 Inches Minimum And 0.235 Inches Maximum Width Between Flats: 0.615 Inches Minimum And 0.627 Inches Maximum Grip Diameter: 0.4358 Inches Minimum And 0.4367 Inches Maximum Single Shear Strength: 14300 Pounds Per Square Inch Nominal Thread Diameter: 0.438 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Fastener Length: Head Style: Hexagon Head Height: 0.203 Inches Minimum And 0.235 Inches Maximum Width Between Flats: 0.615 Inches Minimum And 0.627 Inches Maximum Grip Diameter: 0.4358 Inches Minimum And 0.4367 Inches Maximum Single Shear Strength: 14300 Pounds Per Square Inch Nominal Thread Diameter: 0.438 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Head Style: Hexagon Head Height: 0.203 Inches Minimum And 0.235 Inches Maximum Width Between Flats: 0.615 Inches Minimum And 0.627 Inches Maximum Grip Diameter: 0.4358 Inches Minimum And 0.4367 Inches Maximum Single Shear Strength: 14300 Pounds Per Square Inch Nominal Thread Diameter: 0.438 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Head Height: 0.203 Inches Minimum And 0.235 Inches Maximum Width Between Flats: 0.615 Inches Minimum And 0.627 Inches Maximum Grip Diameter: 0.4358 Inches Minimum And 0.4367 Inches Maximum Single Shear Strength: 14300 Pounds Per Square Inch Nominal Thread Diameter: 0.438 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Width Between Flats: 0.615 Inches Minimum And 0.627 Inches Maximum Grip Diameter: 0.4358 Inches Minimum And 0.4367 Inches Maximum Single Shear Strength: 14300 Pounds Per Square Inch Nominal Thread Diameter: 0.438 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Grip Diameter: 0.4358 Inches Minimum And 0.4367 Inches Maximum Single Shear Strength: 14300 Pounds Per Square Inch Nominal Thread Diameter: 0.438 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Single Shear Strength: Nominal Thread Diameter: Grip Length: 0.438 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 14300 Pounds Per Square Inch 160000 Pounds Per Square Inch
Nominal Thread Diameter: 0.438 Inches Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Grip Length: O.865 Inches Minimum And O.885 Inches Maximum Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch
Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Minimum Tensile Strength: 160000 Pounds Per Square Inch
Hardness Batings
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unf
Specification/standard Data: 80205-nas464 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS464P7A14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS464P7A14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS464P7A14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS464P7A14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/nas464P7A14 and selecting the fasteners.