

## **P/N NAS464P7LA16**

## **Description**

Fastener Length: 1-29/64", Thread: 7/16-20, Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS464P7LA16

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-150-3421

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS464P7LA16 Specifications

3a
Right-hand
0.406 Inches Minimum And 0.453 Inches Maximum
1.406 Inches Minimum And 1.453 Inches Maximum
Hexagon
0.203 Inches Minimum And 0.235 Inches Maximum
0.615 Inches Minimum And 0.627 Inches Maximum
0.4358 Inches Minimum And 0.4367 Inches Maximum
14300 Pounds Per Square Inch
0.438 Inches
1.000 Inches Nominal
20
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd
Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Unf
80205-nas464 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS464P7LA16">https://military-fasteners.com/bolts/machine+bolts/NAS464P7LA16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.