

**Description**

Fastener Length: 4-59/64", Thread: 1/2-20, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS464P8A72
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-585-6667
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS464P8A72 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.422 Inches Nominal
<b>Fastener Length:</b>	4.922 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.234 Inches Minimum And 0.266 Inches Maximum
<b>Width Between Flats:</b>	0.740 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.499 Inches Nominal
<b>Single Shear Strength:</b>	18650 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	4.500 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	9250 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Part Name Assigned By Controlling Agency:</b>	Bolt - Shear, Close Tolerance
<b>Special Features:</b>	No Cotter Pin Hole In Bolt
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P8A72> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.