

Description

Fastener Length: 4-59/64", Thread: 1/2-20, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS464P8A72
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-585-6667
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS464P8A72 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.422 Inches Nominal
Fastener Length:	4.922 Inches Nominal
Head Style:	Hexagon
Head Height:	0.234 Inches Minimum And 0.266 Inches Maximum
Width Between Flats:	0.740 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.499 Inches Nominal
Single Shear Strength:	18650 Pounds Per Square Inch
Nominal Thread Diameter:	0.500 Inches
Grip Length:	4.500 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	9250 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Grip
Part Name Assigned By Controlling Agency:	Bolt - Shear, Close Tolerance
Special Features:	No Cotter Pin Hole In Bolt
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P8A72> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.