

Description

Fastener Length: 1-1/2", Thread: 9/16-18, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS464P9A16
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-585-6679
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS464P9A16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	1.500 Inches Nominal
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Diameter:	0.562 Inches Nominal
Single Shear Strength:	23600 Pounds Per Square Inch
Nominal Thread Diameter:	0.563 Inches
Grip Length:	1.000 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	11800 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Grip
Part Name Assigned By Controlling Agency:	Bolt - Shear, Close Tolerance
Special Features:	No Cotter Pin Hole In Bolt
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS464P9A16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.