

Description

Fastener Length: 1-13/16", Thread: 3/8-24, Thread Length: 1-13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS467628
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-200-2056
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093460, Bolts / Nuts Noi Bbc / Zinc

NO IMAGE
AVAILABLE

P/N NAS467-6-28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.667 Inches Minimum And 1.813 Inches Maximum
Fastener Length:	1.750 Inches Minimum And 1.813 Inches Maximum
Head Style:	Hexagon
Head Height:	0.209 Inches Minimum And 0.229 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Material:	Copper Alloy 462 Overall Or Copper Alloy 464 Overall Or Copper Alloy 482 Overall Or Copper Alloy 485 Overall
Material Document And Classification:	Qq-b-637 Fed Spec Single Material Response Overall
Surface Treatment:	Tin Overall
Surface Treatment Document And Classification:	Ams2408 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas467 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS467-6-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.