

**Description**

Fastener Length: 1-13/16", Thread: 3/8-24, Thread Length: 1-13/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS467628
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-200-2056
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093460, Bolts / Nuts Noi Bbc / Zinc



\* See page 2 for technical characteristics

## P/N NAS467-6-28 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.667 Inches Minimum And 1.813 Inches Maximum
<b>Fastener Length:</b>	1.750 Inches Minimum And 1.813 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.209 Inches Minimum And 0.229 Inches Maximum
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.565 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Material:</b>	Copper Alloy 462 Overall Or Copper Alloy 464 Overall Or Copper Alloy 482 Overall Or Copper Alloy 485 Overall
<b>Material Document And Classification:</b>	Qq-b-637 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Tin Overall
<b>Surface Treatment Document And Classification:</b>	Ams2408 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas467 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS467-6-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.