

Description

length: 0.511", grip: 0.188", thread: 10-32, 100°, close tolerance bolt - reduced head short thread - cadmium plated alloy steel - tri-slot recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS47033
Minimum Qty (MOQ):	50
NSN:	5305-01-263-1683



P/N NAS4703-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.496 Inches Minimum And 0.526 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.303 Inches Nominal
Head Height:	0.040 Inches Nominal
Grip Diameter:	0.1881 Inches Minimum And 0.1887 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Assn Std Single Material Response Overall Or Mil-s-6049 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 11,cl 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4703-3 Professional/industrial Association Specification

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4703-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.