

Description

length: 0.573", grip: 0.250", thread: 10-32, close tolerance, reduced head short thread, cadmium plated alloy steel, tri-slot recess, NAS4703 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS47034
Minimum Qty (MOQ):	50
NSN:	5305-01-259-1195
ECCN:	EAR99



P/N NAS4703-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.563 Inches Minimum And 0.583 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.266 Inches Minimum And 0.303 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.1900 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall And Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4703 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4703-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.