

Description

Fastener Length: 29/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4903U2
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-195-8381
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS4903U2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.433 Inches Minimum And 0.463 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.266 Inches Minimum And 0.303 Inches Maximum
Head Height:	0.049 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Mil Spec Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4903 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4903U2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.