

Description

Fastener Length: 13/16", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4903U8
Minimum Qty (MOQ):	25 EA
NSN:	5306-01-585-4675
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS4903U8 Specifications

Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.823 Inches Nominal
Head Style:	Fillister Countersunk
Head Diameter:	0.303 Inches Maximum
Head Height:	0.012 Inches Maximum
Grip Diameter:	0.181 Inches Minimum And 0.184 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.500 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt 100 Deg Reduced Head, Tri Slot Recess, Close Tolerance, 6al-4v Titanium Alloy Short Thread, Nonlocking
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4903U8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.