

**Description**

Fastener Length: 13/16", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS4903U8
Minimum Qty (MOQ):	25 EA
NSN:	5306-01-585-4675
Schedule B:	8108.90.3060
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS4903U8 Specifications

<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.823 Inches Nominal
<b>Head Style:</b>	Fillister Countersunk
<b>Head Diameter:</b>	0.303 Inches Maximum
<b>Head Height:</b>	0.012 Inches Maximum
<b>Grip Diameter:</b>	0.181 Inches Minimum And 0.184 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.500 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Bolt 100 Deg Reduced Head, Tri Slot Recess, Close Tolerance, 6al-4v Titanium Alloy Short Thread, Nonlocking
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4903U8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.