

P/N NAS4904U6

Description

Fastener Length: ", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS4904U6
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-518-9353
Schedule B:	8108.90.3060
FCCN:	FAR99



^{*} See page 2 for technical characteristics

P/N NAS4904U6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	0.745 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.355 Inches Minimum And 0.397 Inches Maximum
Head Height:	0.063 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.375 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Mil Spec Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS4904U6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.