

Description

Fastener Length: 25/64", Thread: 8-32, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS50021 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-263-1686 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS5002-1 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.222 Inches Nominal |
| Fastener Length: | 0.371 Inches Minimum And 0.401 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.088 Inches Minimum And 0.102 Inches Maximum |
| Grip Diameter: | 0.1626 Inches Minimum And 0.1636 Inches Maximum |
| Single Shear Strength: | 95000 Pounds Per Square Inch |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.052 Inches Minimum And 0.072 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp 3140 Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 11,cl 2 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas5002-1 Professional/Industrial Association Specification |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS5002-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.