

Description

Fastener Length: 25/64", Thread: 8-32, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS50021
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-263-1686
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS5002-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.222 Inches Nominal
Fastener Length:	0.371 Inches Minimum And 0.401 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.088 Inches Minimum And 0.102 Inches Maximum
Grip Diameter:	0.1626 Inches Minimum And 0.1636 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 3140 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 11,cl 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas5002-1 Professional/Industrial Association Specification

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS5002-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.