

Description

length: 0.511", grip: 0.188", thread: 8-32, close tolerance pan head bolt - cadmium plated alloy steel - tri-slot recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS50023
Minimum Qty (MOQ):	10
NSN:	5305-01-196-3196



* See page 2 for technical characteristics

P/N NAS5002-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.331 Inches Nominal
Fastener Length:	0.496 Inches Minimum And 0.526 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.308 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.088 Inches Minimum And 0.102 Inches Maximum
Grip Diameter:	0.1621 Inches Minimum And 0.1627 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.170 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 3140 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas5002 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS5002-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.